

Application serial No. 09/611,447  
Office Action dated September 9, 2005  
Response dated November 2, 2005

**In the Claims:**

This listing of claims will replace all prior versions, and listings, of the claims in the application.

**Listing of Claims:**

1. (currently amended) In a data communication network comprising a plurality of optical label switching routers and fiber optic links between said optical label switching routers, a method of representing optical network bandwidth, said method comprising:

assigning an optical label to a channel group, said channel group using one of said fiber optic links and comprising a plurality of channels, said label representing an ingress to egress mapping;

encoding said optical label so as to comprise a type field, a length field and a value field, where said value field comprises a label component and where said label component comprises an indication of whether each channel of said plurality of channels is available for use in a label switched path.

2. (previously presented) The method of claim 1 wherein said indication of whether each channel of said plurality of channels is available for use in a label switched path identifies said one of said fiber optic links and a wavelength on said one of said fiber optic links.

3. (currently amended) In a data communication network comprising a plurality of optical label switching routers and fiber optic links between said optical label switching routers, a method of representing optical network bandwidth, said method comprising:

assigning an optical label to a channel group, said channel group using one of said fiber optic links and comprising a plurality of channels, said label representing an ingress to egress mapping;

encoding said optical label so as to comprise a type field, a length field and a value field, where said value field comprises a label component and where said label

Application serial No. 09/611,447  
Office Action dated September 9, 2005  
Response dated November 2, 2005

component comprises an indication of currently available bandwidth on each of said plurality of channels;

wherein said indication of currently available bandwidth identifies said one of said fiber optic links, a wavelength on said one of said fiber optic links and said channel group.

4. (previously presented) The method of claim 3 wherein current availability of bandwidth on each of said plurality of channels is represented by a single bit.

5. (previously presented) The method of claim 4 wherein a bit value of zero for said single bit indicates currently available bandwidth on a given one of said plurality of channels.

6. (currently amended) In a first data communication network comprising a plurality of optical label switching routers and fiber optic links between said optical label switching routers, said label representing an ingress to egress mapping, a method of representing traffic characteristics comprising:

encoding a representation of traffic characteristics of an interface between one of said optical label switching routers in said first data communication network and a node in a second network so as to comprise a type field, a length field and a value field, where said value field comprises an attribute of said second network.

7. (previously presented) The method of claim 6 wherein said attribute comprises an indication of a service type of said second network.

8. (previously presented) The method of claim 6 wherein said attribute comprises an indication of a control protocol of said second network.

9. (currently amended) In a data communication network comprising a plurality of optical label switching routers and fiber optic links between said optical label switching routers, said label representing an ingress to egress mapping, a method of representing characteristics of an optical trail, said method comprising:

encoding a representation of said characteristics of said optical trail so as to comprise a

Application serial No. 09/611,447  
Office Action dated September 9, 2005  
Response dated November 2, 2005

type field, a length field and a value field, where said value field comprises a channel group description; and

where said channel group description comprises an indication of channel group type and an indication of a number of members in said channel group.

10. (currently amended) In a data communication network comprising a plurality of optical label switching routers and fiber optic links between said optical label switching routers, said label representing an ingress to egress mapping, a method of specifying session parameters for an optical communication session over one of said fiber optic links, where said one of said fiber optic links originates at an originating label switching router, said method comprising:

encoding a specification of said session parameters so as to comprise a type field, a length field and a value field, where said value field comprises a range component; and

said range component comprises:

an identity of one of said fiber optic links;

a lower bound of a block of wavelengths supported by said originating label switching router on said one of said fiber optic links; and

an upper bound of said block of wavelengths supported by said originating label switching router on said one of said fiber optic links.

11-15 (cancelled)

16. (currently amended) An optical label switching router operable to:

assign an optical label to a channel group, said channel group using one of a plurality of fiber optic links and comprising a plurality of channels, said label representing an ingress to egress mapping;

encode said optical label so as to comprise a type field, a length field and a value field, where said value field comprises a label component and where said label component

Application serial No. 09/611,447  
Office Action dated September 9, 2005  
Response dated November 2, 2005

comprises an indication of whether each channel of said plurality of channels is available for use in a label switched path.

17. (cancelled)

18. (currently amended) An optical label switching router operable to:

encode a representation of characteristics of an optical trail of a channel group so as to comprise a type field, a length field and a value field, where said value field comprises a description of said channel group; and

where said description of said channel group comprises an indication of a type of said channel group and an indication of a number of members in said channel group; said label representing an ingress to egress mapping.

19. (currently amended) An optical label switching router operable to:

encode a specification of session parameters for an optical communication session over a fiber optic link so as to comprise a type field, a length field and a value field, where said value field comprises a range component, said label representing an ingress to egress mapping;

where said range component comprises:

an identity said fiber optic link;

a lower bound of a block of wavelengths supported by said label switching router on said fiber optic link; and

an upper bound of said block of wavelengths supported by said label switching router on said fiber optic link.

20. (currently amended) A computer readable medium for providing program control for an optical label switching router, said computer readable medium adapting said optical label switching router to be operable to:

Application serial No. 09/611,447  
Office Action dated September 9, 2005  
Response dated November 2, 2005

assign an optical label to a channel group, said channel group using one of a plurality of fiber optic links and comprising a plurality of channels, said label representing an ingress to egress mapping;

encode said optical label so as to comprise a type field, a length field and a value field, where said value field comprises a label component and where said label component comprises an indication of whether each channel of said plurality of channels is available for use in a label switched path.

21. (cancelled)

22. (currently amended) A computer readable medium for providing program control for an optical label switching router, said label representing an ingress to egress mapping, said computer readable medium adapting said optical label switching router to be operable to:

encode a representation of characteristics of an optical trail of a channel group so as to comprise a type field, a length field and a value field, where said value field comprises a description of said channel group; and

where said description of said channel group comprises an indication of a type of said channel group and an indication of a number of members in said channel group.

23. (currently amended) A computer readable medium for providing program control for an optical label switching router, said label representing an ingress to egress mapping, said computer readable medium adapting said optical label switching router to be operable to:

encode a specification of session parameters for an optical communication session over a fiber optic link so as to comprise a type field, a length field and a value field, where said value field comprises a range component; and

where said range component comprises:

an identity said fiber optic link;

Application serial No. 09/611,447  
Office Action dated September 9, 2005  
Response dated November 2, 2005

a lower bound of a block of wavelengths supported by said label switching router on said fiber optic link; and

an upper bound of said block of wavelengths supported by said label switching router on said fiber optic link.